MODEL: DPM-P



Features	
Standard Marking Area	25mm x 90mm
Marking Speed	30mm~40mm/s
Repeatability	0.01mm
Marking Depth	0.1mm~0.5mm (According to material)
Power Supply	AC 220V 50HZ
Temperature	0 to 40 Degree Centigrade
Air pressure required	0.2Mpa ~ 0.6Mpa (2-4 bars)
Marking type	All English Alphabets, All Numbers,
	Variety of Graphics, Logos, Barcodes
System OS requirement	Windows 7- 32 bit OS
Job Holding	By Electromagnets

DPM-T

bnomoib



MODEL: DPM-T

Features	
Standard Marking Area	140mm x70mm
Marking Speed	30mm to 40mm
Repeatability	0.01mm
Marking Depth	0.1mm~0.5mm (According to material)
Power Supply	AC 220V 50HZ
Temperature	0 to 40 Degree Centigrade
Air pressure required	0.2Mpa ~ 0.6Mpa (2-4 bars)
Chuck Dia	100mm Diameter
Marking type	All English Characters, All Numbers,
	Variety of Graphics, Logos, Barcodes
System OS requirement	Windows 7- 32 bit OS
Mounting Table Optional	

- You can also avail our service on CNC controllers, Servo drives, Ballscrews, Linear scales, DRO systems, Cable Drag Chains, Rotary Engraving Tool, Laser Engraving, Optical Profile Projector(OPP), Video Measuring System(VMS), etc.
- We Can Also Design / Manufacturer CNC Special Purpose Machine(SPM's) According to your requirement with reliable Cost effective CNC controller and servo motors.
- We would like to register our company name to your vendor list.

For further technical information please contact





DIAMOND ENGINEERING